


FEATURES:

- 6dB Hybrid Combiner (4x4 Hybrid) Modules **IDR Series** DRAN system
- 100W per Port of power handling
- Minimum 24dB Isolation
- **-163dBc PIM** with Low Insertion Loss
- Interchangeable Modules for easy upgrades



ELECTRICAL SPECIFICATIONS:

Part Numbers	Freq Bands							
	600(B71) 700-Cell	700-FN (B14)	850	PCS	AWS-1 AWS-3	WCS	BRS	DoD CBRS C-Band
R232H-600-6000-D43	Covers all Bands (600MHz – 6000MHz)							
Coupling Loss	6.20 dB ± 0.80dB @ 600-2700 MHz 6.20 dB ± 0.80dB @ 2700-4200 MHz 6.35 dB ± 0.80dB @ 4200-6000 MHz							
Isolation	25dB @ 600-3800 MHz 24dB @ 3800-6000 MHz							
VSWR	1.25:1							
Impedance	50 Ohms							
Input Power / Port	100 Watts (Avg)							
Intermodulation (PIM - 3 rd)	-163dBc (2 Tones +43 dBm)							
Connectors	4.3-10 or Nex10							
Temperature	-30°C to +70°C							
Rack Tray Dimensions	13.95”(W) x 1.725”(H) x 5.00”(D)							

Please contact our sales department at 737-200-7090 or sales@InnowaveRF.com for any custom requirements.

© Innowave RF, LLC. All Rights Reserved. Specs can change without notice. Drawings are for reference purpose only.