


Innovation in Every Wave

FEATURES:

- 2x Triplexer Modules for H-Frame / Rack-Mounted DRAN system
- **2x2 MIMO** solution with 2 combiners on a tray
- Up to 3 bands can be combined per Carrier
- Minimum 40dB Isolation
- **1RU** Rack High
- **-161dBc PIM** with Low Insertion Loss
- Interchangeable Modules for easy upgrades

ELECTRICAL SPECIFICATIONS:

Freq Bands	600(B71) 700-Cell	700-FN (B14)	850	PCS	AWS-1 AWS-3	WCS	BRS	DoD CBRS C-Band
Part Numbers								
R932H-800-2100-D43	PORT 1	PORT 1	PORT 2	PORT 3	PORT 3			
R932H-1400-2490-D43	PORT 1	PORT 1	PORT 1	PORT 2	PORT 2	PORT 3	PORT 3	
R932H-1444-2390-D43	PORT 1	PORT 1	PORT 1	PORT 2	PORT 3	PORT 3		
R932H-1444-3390-D43	PORT 1	PORT 1	PORT 1	PORT 2	PORT 2	PORT 2	PORT 2	PORT 3
R932H-1500-3390-D43	PORT 1	PORT 1	PORT 1	PORT 1	PORT 1	PORT 2	PORT 2	PORT 3
R932H-1600-2390-D43	PORT 1	PORT 1	PORT 1	PORT 1	PORT 1	PORT 2	PORT 3	
R932H-1600-3390-D43	PORT 1	PORT 1	PORT 1	PORT 1	PORT 1	PORT 1	PORT 2	PORT 3
R932H-1800-2490-D43				PORT 1	PORT 2	PORT 3	PORT 3	
R932H-1800-3390-D43				PORT 1	PORT 2	PORT 3	PORT 3	PORT 3
R932H-1900-3390-D43				PORT 1	PORT 1	PORT 2	PORT 2	PORT 3
R932H-2500-3800-D43							PORT 1	PORT 2 (DoD) PORT 3 (C-Band)
Passband Insertion Loss	0.35 dB							
Isolation	≥40 dB							
Return Loss	20 dB							
Impedance	50 Ohms							
Input Power /Port	150 Watts (Avg)							
Intermodulation (PIM - 3 rd)	-161dBc (2 Tones +43 dBm)							
Connectors	4.3-10 or Nex10							
Temperature	-30°C to +70°C							
Rack Height	1RU							
Rack Tray Dimensions	19.00"(W) x 1.75"(H) x 9.50"(D)							
*** For any other combination of bands, please contact us. ***								

Please contact our sales department at 737-200-7090 or sales@InnowaveRF.com for any custom requirements.

© Innowave RF, LLC. All Rights Reserved. Specs can change without notice. Drawings are for reference purpose only.